

**Product Data Sheet**

# ASILGRIP

**ASILGRIP** is a synthetic, mineral, environment-friendly gritting material on the basis of aluminium silicate glass melt, with the following technical details:

## CHEMICAL ANALYSIS

Aluminium silicate glass melt;  
chemical composition calculated as oxides:

Silicon dioxide	42 – 58 %
Aluminium oxide	23 – 32 %
Iron (III) oxide	3 – 15 %
Calcium oxide	2 – 8.5 %
Potassium oxide	0.5 – 4.6 %

The metals present are chemically bound in the form of silicates or aluminates.

## CONTAINS NO WATER-SOLUBLE CONSTITUENTS

## CONTAINS NO FREE CRYSTALLINE SILICIC ACID

Specific weight/ grain density	2.4 – 2.6 kg/dm <sup>3</sup>
Bulk density, for standard grain sizes	1.05 – 1.4 kg/dm <sup>3</sup>
Mohs hardness	min. 7

## SPECIAL FEATURE

EG certificate of compliance with DIN EN 13043 is available for ASILGRIP 1 - 3.

## USE

- Gritting material

## FIELDS OF APPLICATION

- Asphalt pavement industry

## GRAIN SIZES

- on request

## PACKING

- 25 kg paper bags on EURO pallets
- 1,000 kg/ 1,500 kg big bags
- in bulk

January 2019

STEAG Power Minerals GmbH  
Duisburger Str. 170  
46535 Dinslaken, Germany  
E-Mail: pqa@steag.com

